

60W 1000Mbps PoE Injector



Product Highlights

- Support 1* 1000Mbps PoE power supply port+1* 1000Mbps RJ45 port
- Compatible with IEEE802.3af (15.4W), IEEE802.3at (30W), and IEEE802.3bt (60W)
- Supports AC 100-240V power supply
- Metal casing, IP20 protection level, operating temperature range of -20 to 50 ° C
- Support port surge: differential mode 2KV, common mode 6KV; Electronic ESD: Contact discharge 6KV, air discharge 8KV

Hardware Features

Description	Specification
Model	HR-BTG-N601
Interface	1* 1000Mbps PoE Port 1* 1000Mbps RJ45 Port
Port Standard	IEEE802.3af /IEEE802.3at/IEEE802.3bt
Single Port Max	15.4 W (IEEE 802.3af) 30 W (IEEE 802.3at) 60 W (IEEE 802.3bt)
Industry Standard	EN61000-4-2 (ESD) IEN61000-4-5 (Surge) EN61000-4-3 (RS) EN61000-4-6 (CS) EN61000-4-4 (EFT)
Protection Grade	IP20
PoE Port Output Voltage	DC 52V
Power Supply	AC 100-240V 50/60Hz DC 52V/1.25A
PoE Standard	IEEE802.3af (15.4W) IEEE802.3at (30W) IEEE802.3bt (60W)
Structure Information	Product Dimensions:187mm* 95mm*40 mm Packaging Dimensions: 245mm*190mm*60mm Product Net Weight: 0.486KG Product Gross Weight:0.712KG
Packing Information	Carton Dimensions:520mm*320mm*400mm Packing Quantity: 20PCS Packing Weight: 15.24KG
Package Content	Injector 1pcs, manual 1pcs, certificate of qualification 1pcs
Certification	CE、FCC、RoHS
Installation	Wall Mounting
Operating Temperature	-20~50°C
Storage Temperature	-40~85°C
Operation Humidity	5%~90%, non condensing
Storage Humidity	5%~95%, non condensing

Product Structure Diagram

