

6-Port Gigabit Industrial Managed Switch



Product Highlights

- Support 4*1Gbps RJ45 ports+2*2.5Gbps SFP ports+1*Console port
- Support: IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3z / AB, IEEE802.1Q, IEEE802.1p, IEEE802.1d/w
- Support Spanning Tree STP (802.1D) and RSTP (802.1w), MSTP (802.1s), ERPS
- Support SNMP v1/v2/v3 Simple Network Management Protocol
- Support IGMP Snooping, static multicast filtering, and MLD Snooping filtering
- Support 802.1x port authentication and AAA authentication to enhance network security
- Support WEB, Telnet, CLI, SSH management
- IP40 protection level, high-strength aluminum profile shell, DIN35 rail installation
- Industrial grade 4-level design, operating temperature from -40~75°C
- Support redundant power supply connection and anti reverse connection
- Comply with EMC EN55032 standard

Hardware Features

Description	Specification
Model	HR600-SWG2042AS
Interface	4*1Gbps RJ45 ports 2*2.5Gbps SFP ports(comply with 155M/1.25Gbps) 1*Console port
Port Standard	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE 802.3ab (Gigabit Ethernet) IEEE 802.3z (Gigabit Ethernet Fiber Standard) IEEE802.3x (Flow Control) IEEE 802.1w Rapid Spanning Tree Protocol IEEE 802.1D Spanning Tree Protocol
Switching Bandwidth	18Gbps
Packet Forwarding Rate	13.39Mpps
Packet Buffer	4Mbit
MAC Address Table	8K
Jumbo Frame	Up to 9600bytes
VLAN	VLAN range 1-4094, maximum active VLAN is 4K
Transmission Method	Store and Forward
Surge Protection	Port Surge: Common mode 6KV, Differential mode 2KV Electrostatic ESD: Air 15KV, Contact 8KV (Class C)
Operating Temperature	-40~75°C
Storage Temperature	-40~85°C
Operation Humidity	10%~90%, non condensing
Storage Humidity	5%~95%, non condensing
Power Supply	DC12~55V Power wiring: 4 PIN industrial terminals (redundant V1+V1-, V2+V2-)
Mainboard Power Consumption	6.278W

Hardware Features

Description	Specification
Structure Information	Product Dimensions: 145*108*40 mm Packaging Dimensions: 245*190*60mm Product Net Weight: 0.58KG Product Gross Weight: 0.78KG(excluding power supply)
Packing Information	Carton Dimensions: 520*320*400mm Packing Quantity: 20PCS Packing Weight: 17KG
Package Contents	Switch 1pcs, Manual 1pcs, Certificate of Inspection 1pcs, Serial cable 1pcs
Fan Quantity	0
Installation	Desktop, Wall mounting installation, Rail installation
PWR	On: Powered on Off: Powered off
SYS	On: The system is running normally Flashing: System startup in progress
Ports 1-4 Yellow LED	On: 1Gbps Link normal Off: Link blocked Flashing: Data transmitting
Ports 1-4 Green LED	On: 10/100Mbps Link normal Off: Link blocked Flashing: Data transmitting
Ports G5-G6	On: Fiber optic link normal Off: Fiber optic link blocked Flashing: Link data transmission
Reset	Short press to restart, long press for 6 seconds to restore factory settings

Software Features

Description	Specification
L2 Function	
IPv4	IPv4 VLAN Interface IPv4 Static Routes ARP
Port	Port Switch configuration Port Description configuration Port Speed configuration Port Duplex configuration Port Flow Control configuration Max. 2500Mbps at SFP interface Jumbo Frame EEE Fiber Module(DDM)
Link Aggregation	Support load balance policy; Base on MAC and IP-MAC Static and Dynamic Group Support LACP
Storm Control	Boardcast suppression Unknown Multicast Unknown Unicast
Port Mirroring	One to one monitor Many to one monitor Ingress/Egress/Both
Port Security	MAC Address Constraints Action:Trap/Shutdown
Port Isolation	Support
Port Rate-limit	Support
Loopback Detection	Support
VLAN	Access/Trunk/Hybrid VLAN Tunnel (Q-in-Q Tunnel) GVRP VLAN range 1-4094, maximum active VLAN is 4K

Software Features

Description	Specification
MAC Address	Dynamic MAC address
	Static MAC address
Spanning Tree Protocol	STP/RSTP/MSTP
	BPDU Filter
	BPDU Guard
	Edge Port
ERPS	Major and sub ring
	up to 16 rings
Smart Ring	Private Ring
	Major and sub ring
	Up to 16 rings
PTP	Ordinary Clock
	Boundary Clock
	Transparent clock
LLDP	Support
Multicast	IGMP Snooping
	IGMP V1/V2/V3
	Router Port
	Static IGMP group address
	IGMP groups filtering
	Querier
QoS	MLD Snooping
	Traffic classification based, Strict priority and WRR
	Port Priority
	802.1P Priority
	IP DSCP Priority
	Support up to 8 queues per port
Port Shaping	

Software Features

Description	Specification
Services	
DHCP	DHCP Server IP Pool Static Binding DHCP Relay
Access Protocol	HTTP Telnet
	SSH Manager ACL
Security	
AAA	RADIUS TACACS+ 802.1X Base on port/MAC/local/WEB
DHCP Snooping	Support

Software Features

Description	Specification
IP Source Guard	Support
Dynamic ARP Inspection	Support
ACL	MAC ACL
	Port ACL
	IPv4 ACL
	IPv6 ACL
Diagnostics	
Syslog	Logging Message
	Remote Server
Ping	Support
Traceroute	Support
Cable Diagnostics	Support
Equipment Management	
Manager Access	Console
	HTTP
	Telnet
	SSHv2
	SNMP
Manager IP	Static Address
	DHCP Client
	Support IPv4 and IPv6 address
	DNS
	SNTP
Time Synchronization	
SNMP	Manual Time
	V1/V2C/V3
	Community
SNMP	V3 User
	Group
	Trap Host

Software Features

Description	Specification
SNMP MIB	RFC 1213 MIB-II
	RFC 1493 Bridge MIB
	RFC 1643 Ethernet MIB
	RFC 2819 RMON MIB (Groups 1, 2, 3 and 9)
	RFC 2863 Interface MIB
	Private MIB
RMON	Statistics
	History Configuration
	Event Configuration
	Alarm Configuration
User Management	Congurable user privilege level from 0 - 15
Firmware Management	Firmware upgrade
	Double Image; Swap between Active and Alternate firmware image.
Configuration Management	Upload and download
Save	Support
Restart	Support
Factory Defaults	Support
Standard Compliance	
IEEE 802.3x flow control and back pressure	
IEEE 802.3ad port trunk with LACP	
IEEE 802.1D Spanning Tree Protocol	
IEEE 802.1w Rapid Spanning Tree Protocol	
IEEE 802.1s Multiple Spanning Tree Protocol	
IEEE 802.1p Class of Service	
IEEE 802.1Q VLAN tagging	
IEEE 802.1x Port Authentication Network Control	
IEEE 802.1ab LLDP	
RFC 768 UDP	
RFC 793 TFTP	
RFC 791 IP	

Software Features

Description	Specification
RFC 792 ICMP	
RFC 2068 HTTP	
RFC 1112 IGMP v1	
RFC 2236 IGMP v2	
RFC 3376 IGMP v3	
RFC 2710 MLD v1	
RFC 3810 MLD v2	

Product Structure Diagram

