
28-Port Gigabit Industrial Managed Switch



Product Highlights

- Support: IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3z / ab, IEEE802.1Q, IEEE802.1p, IEEE802.1d/w
- Support SNMP v1/v2/v3 Simple Network Management Protocol
- Support IGMP Snooping, static multicast filtering, and MLD Snooping filtering
- Support 802.1x port authentication and AAA authentication to enhance network security
- Support WEB, Telnet, CLI, SSH management
- IP40 protection level, high-strength aluminum shell, DIN35 rail installation
- Industrial grade 4-level design, operating temperature from -40~75°C
- Support redundant power supply connection and anti reverse connection

Copyright © 2025 Shenzhen HongRui Technology Co.,Ltd

Hardware Features

Description	Specification
Model	HR722S-24T4GS
Interface	24*1Gbps RJ45 ports 4*1Gbps SFP ports 1*Console port
Port Standard	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE 802.3ab (Gigabit Ethernet) IEEE 802.3z (Gigabit Ethernet Fiber Standard) IEEE802.3x (Flow Control) IEEE 802.1w Rapid Spanning Tree Protocol IEEE 802.1D Spanning Tree Protocol
Switching Bandwidth	56Gbps
Packet Forwarding Rate	41.66Mpps
Packet Buffer	4.1Mbit
MAC Address Table	8K
Jumbo Frame	10Kbytes
VLAN	VLAN range 1-4094, maximum active VLAN is 4K
Transmission Method	Store and Forward
Power Supply	DC12~55V Power wiring: 4 PIN industrial terminals (redundant V1+V1-, V2+V2-)
Relay	Reserved relay (3pin terminal block), relay protection: Common mode 2KV, Differential mode 1KV
Certification	CE, FCC, RoSH

Copyright © 2025 Shenzhen HongRui Technology Co.,Ltd

Hardware Features

Description	Specification
Mainboard Power Consumption	21.16W
Structure Information	Product Dimensions: 186.6*122.7*86mm Packaging Dimensions: 245*190*103mm Product Net Weight: 1.18KG Product Gross Weight: 1.34KG
Packing Information	Carton Dimensions: 555*405*270mm Packing Quantity: 10PCS Packing Weight: 14.4KG
Package Contents	Switch 1pcs, Serial cable 1pcs, Manual 1pcs, Certificate of Inspection 1pcs
Fan Quantity	0
Installation	Desktop, Wall mounting installation, Rail installation
Surge Protection	Port Surge: Common mode 6KV, Differential mode 2KV Electrostatic ESD: Air 15KV, Contact 8KV(Class C) Power Port : Common mode 2KV, Differential mode 1KV
Operating Temperature	-40~75°C
Storage Temperature	-40~85°C
Operation Humidity	10%~90%, non condensing
Storage Humidity	5%~95%, non condensing
PWR Green LED	On: Powered on Off: Powered off
SYS Green LED	Flashing: System startup in progress On: The system is running normally
Ports 1-24 LED	Green LED on: 1000Mbps Link normal Yellow LED on:10/100Mbps Link normal Off: Link blocked Fast Flashing: Data transmitting
Ports 25-28 Green LED	On: 1000Mbps Link normal Off: Link blocked Flashing: Data transmitting
Reset	Short press to restart, long press for 6 seconds to restore factory settings

Copyright © 2025 Shenzhen HongRui Technology Co.,Ltd

Software Features

Description	Specification
L2+ Function	
IPv4	IPv4 VLAN Interface IPv4 Static Routes ARP
IPv6	IPv6 VLAN Interface IPv6 Static Routes IPv6 ND
L2 Function	
Port	Port Switch configuration Port Description configuration Port Speed configuration Port Duplex configuration Port Flow Control configuration Jumbo Frame EEE Fiber Module(DDM)
Link Aggregation	Support load balance policy; Base on MAC and IP-MAC Static and Dynamic Group Up to 8 groups Support LACP
Storm Control	Boardcast suppression Unknown Multicast Unknown Unicast
Port Mirroring	One to one monitor Many to one monitor Ingress/Egress/Both Up to 4 session groups
Port Security	MAC Address Constraints Port Security MAC Address Protect/Restrict/Shutdown
Port Isolation	Support
Port Rate-limit	Support
Loopback Detection	Support

Copyright © 2025 Shenzhen HongRui Technology Co.,Ltd

Software Features

Description	Specification
VLAN	Access/Trunk/Hybrid VLAN Tunnel (Q-in-Q Tunnel) VLAN range 1-4094, maximum active VLAN is 4K Voice VLAN MAC VLAN Surveillance VLAN Protocol VLAN GVRP
MAC Address	Dynamic MAC address Static MAC address Filtering MAC Address
Spanning Tree Protocol	STP/RSTP/MSTP BPDU Filter BPDU Guard Edge Port
LLDP	LLDP LLDP MED
Multicast	IGMP Snooping IGMP V1/V2/V3 Router Port Static IGMP group address IGMP groups filtering Querier MLD Snooping MVR
QoS	Traffic classification based, Strict priority and WRR Port Priority 802.1P Priority IP TOS Priority IP DSCP Priority Support up to 8 queues per port Priority Remarking

Copyright © 2025 Shenzhen HongRui Technology Co.,Ltd

Software Features

Description	Specification
ERPS	Only SFP port
Services	
DHCP	DHCP Server
	IP Pool
	Static Binding
	Option 43
	DHCP Relay
Access Protocol	HTTP
	HTTPS
	Telnet
	SSHv2
	Manager ACL
	Session Timeout
	Password Retry Count
	Silent Time
Security	
AAA	RADIUS
	TACACS+
	802.1X
	Base on port/MAC/local/WEB
DHCP Snooping	Global/VLAN
	Option 82
	Circuit ID

Copyright © 2025 Shenzhen HongRui Technology Co.,Ltd

Software Features

Description	Specification
IP Source Guard	Support
Dynamic ARP Inspection	Support
DoS	Support
ACL	MAC ACL IPv4 ACL IPv6 ACL
Diagnostics	
Syslog	Logging Message Remote Server
Ping	Support
Traceroute	Support
Copper Test	Support
UDLD	Support
Port Statistics	Support
Equipment Management	
Manager Access	Console HTTP/HTTPS Telnet SSH SNMP
Manager IP	Static Address DHCP Client Support IPv4 and IPv6 address Manager VLAN DNS
Time Synchronization	SNTP Manual Time
SNMP	V1/V2C/V3 Community V3 User Group Trap Host

Copyright © 2025 Shenzhen HongRui Technology Co.,Ltd

Software Features


Description	Specification
SNMP MIB	RFC 1213 MIB-II RFC 1493 Bridge MIB RFC 1643 Ethernet MIB RFC 2819 RMON MIB (Groups 1, 2, 3 and 9) RFC 2863 Interface MIB LLDP Private MIB
RMON	Statistics History Configuration Event Configuration Alarm Configuration
User Management	Support
Firmware Management	Firmware upgrade
Configuration Management	Upload and download
Save	Support
Restart	Support
Factory Defaults	Support
Standard Compliance	
IEEE 802.3x flow control and back pressure	
IEEE 802.3ad port trunk with LACP	
IEEE 802.1D Spanning Tree Protocol	
IEEE 802.1w Rapid Spanning Tree Protocol	
IEEE 802.1s Multiple Spanning Tree Protocol	
IEEE 802.1p Class of Service	
IEEE 802.1Q VLAN tagging	
IEEE 802.1x Port Authentication Network Control	
IEEE 802.1ab LLDP	
RFC 768 UDP	
RFC 793 TFTP	
RFC 791 IP	

Copyright © 2025 Shenzhen HongRui Technology Co.,Ltd

Software Features

Description	Specification
RFC 792 ICMP	
RFC 2068 HTTP	
RFC 1112 IGMP v1	
RFC 2236 IGMP v2	
RFC 3376 IGMP v3	
RFC 2710 MLD v1	
FRC 3810 MLD v2	

Product Structure Diagram



Copyright © 2025 Shenzhen HongRui Technology Co.,Ltd