

# 8-port Gigabit Ethernet Switch



## Product Highlights

- 8\*1G RJ45 ports
- Compliant with IEEE802.3 and IEEE802.3u,IEEE802.3az,IEEE802.3ab standards
- RJ45 port supports 10M/100M/1G adaptive
- Supports automatic port flipping (Auto MDI/MDIX)
- The panel indicator LED will monitor the working status and assist in fault analysis
- Flow control method, IEEE802.3x standard for full duplex and Backpressure standard for half duplex

## Hardware Features

Description	Specification
Model	HR-SWG0080
Interface	8 *1G RJ45 ports
Port Standard	IEEE802.3 (Ethernet)
	IEEE802.3u (Fast Ethernet)
	IEEE802.3x (Flow Control)
	IEEE802.3ab (Gigabit Ethernet)
	IEEE802.3az(Energy Efficient Ethernet)
Switching Capacity	16Gbps
Packet Forwarding Rate	11.9Mpps
Packet Buffer	4Mbit
MAC Address Table	8K
Transmission Method	Store and Forward
Power Supply	AC 100-240V , 50/60Hz
	DC 5V 1A
Mainboard Power Consumption	3.77W
Structure Information	Product Dimensions :138*78*25mm
	Packaging Dimensions :175*120*63mm
	Product Net Weight: 0.24Kg
	Product Gross Weight:0.37Kg
Packing Information	Carton Dimensions :520*335*380mm
	Packing Quantity: 40PCS
	Packing Weight: 15.8KG
Package Contents	switch 1pcs, Power adapter 1pcs, manual 1pcs, certificate of qualification 1pcs
Fan Quantity	0
Installation	desktop
Surge Protection	Surge protection: common mode 2KV, differential mode 1KV (Class A); Electrostatic ESD: air 4KV, contact 3KV (Class C)
Operating Temperature	0~40℃
Storage Temperature	-40 ℃ to 70 ℃
Operation Humidity	10%~90%, non condensing
Storage Humidity	5%~95%, non condensing
PWR LED	Green LED On: Powered on
	Green LED Off: Powered off
1-5 LED	Green LED On:Link normal
	Green LED Off: Link blocked
	Flashing: Data transmitting

Product Structure Diagram

